1471 Corresponding optical module



Overview

The NEW ALCATEL-LUCENT SFP-OC3-1471-30 Compatible 155M/OC3 SFP 80km SMF Transceiver Module are high performance, cost effective modules with low power dissipation, Tx- DFB CWDM,Rx- PIN, Fully compliant with MSA standards, this hot pluggable module can be installed into any. The NEW ALCATEL-LUCENT SFP-OC3-1471-30 Compatible 155M/OC3 SFP 80km SMF Transceiver Module are high performance, cost effective modules with low power dissipation, Tx- DFB CWDM,Rx- PIN, Fully compliant with MSA standards, this hot pluggable module can be installed into any. Fiber optic module panel with a built-in OADM, terminated in LC connectors. The module should be mounted in a 1U or 3U panel. The patch panel comes with 2 pcs. There is room for 12 modules in the 3U panel and 3 modules. CWDM technology provides the flexibility to increase capacity of existing fiber infrastructure by enabling multiple channels/wavelengths over the same fiber cabling. Each channel carries data independently from each other, allowing network designers to transport different data rates. This product. FTLX1471D3BCL 10GBASE-LR SFP+ transceiver with LC Duplex connection according to MSA standards compatible with Finisar (Cisco Code) from the BlueOptics brand. 25G-CWDM-XX-120KM is an industrial grade CWDM SFP module designed specifically for ultra long distance point-to-point network communication. It supports a transmission rate of 1.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Article Content

GE-CWDM eSFP Optical Modules

CWDM-SFPGE-1571 CWDM-SFPGE-1591 CWDM-SFPGE-1611 GE-CWDM eSFP Optical Modules (Used Only in the OADM scenario) GE-DWDM eSFP Optical Modules GE SFP

1471 OADM, SM, LC/PC, fiber optic cassette modul Foss Fiber Optics

Fiber optic module panel with a built-in OADM, terminated in LC connectors. The module should be mounted in a 1U or 3U panel.

Module, 1471 OADM, SM, LC/PC Foss AS

Fiber optic module panel with a built-in OADM, terminated in LC connectors. The module should be mounted in a 1U or 3U panel.

6 Channels 1471-1571nm, Single Fiber CWDM Mux Demux, Side-B,

CWDM Mux Demux is designed to assist network operators with building a fiber foundation for 5G networks. It is equipped with splice closure/distribution box that allows applications in non-controlled

Finisar (Cisco Code) FTLX1471D3BCL SFP+ 10GBASE-LR

This means that, if available from stock, you will immediately receive a corresponding replacement module for your FTLX1471D3BCL compatible 10GBASE-LR LC Duplex SFP+

1.25Gbps, 120km, Duplex LC CWDM SFP Module | Yingda

SFP-1.25G-CWDM-XX-120KM is an industrial grade CWDM SFP module designed specifically for ultra long distance point-to-point network communication. It supports a transmission rate of 1.25Gbps and

FTLX1471 Coherent | Fiber Optic Transceiver Modules

FTLX1471 Coherent Fiber Optic Transceiver Modules parts available at DigiKey.

SNS SFP-OC3-1471-30 -

The NEW ALCATEL-LUCENT SFP-OC3-1471-30 Compatible 155M/OC3 SFP 80km SMF Transceiver Module are high performance, cost effective modules with low power dissipation, Tx-

FTLX1471D3BCL Coherent | Fiber Optic Transceiver Modules | DigiKey

Buy now, ships today. FTLX1471D3BCL - Transceiver Module Ethernet 10Gbps 1310nm 3.3V LC Duplex Pluggable, SFP+ from Coherent. View datasheets, pricing and availability from DigiKey now!

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

1471/1611nm 8-channel Optical CWDM Mux/Demux Module with LC

The product is designed to integrate conveniently with Grass Valley''s FIO-1901, FIO-901 and FIO-991p Series of optical/electrical converters, but is equally useful with any other product working with

Module, 1471/1491 OADM, LC/PC, connected Foss AS

Fiber optic module panel with a built-in OADM, terminated in LC connectors. The module should be mounted in a 1U or 3U panel.

CWDM-8-LC | 1471/1611nm 8-channel Optical CWDM Mux/Demux Module

Product information for 1471/1611nm 8-channel Optical CWDM Mux/Demux Module with LC Connectors CWDM-8-LC manufactured by Grass Valley. Provided by Audio-Video Corporation.

16 Channels 1471-1611nm Dual Fiber CWDM Mux Demux Lgx Module

CCWDM Module Single Fiber The compact coarse wavelength division multiplexer has good thermal stability. There is an aligner between the common end and each channel, and the product has low

1471/1611nm 8-channel Optical CWDM Mux/Demux Module with LC

CWDM mux/demux modules are bidirectional passive optical multiplexers and demultiplexers, allowing multiple optical signals at different wavelengths to pass through a single optical fiber strand. The

FTLX1471D3BTL Datasheet, Features, Pinout, and Applications

The FTLX1471D3BTL is a high-speed 10G Ethernet SFP+ transceiver module designed for optical communication applications. It operates at a wavelength of 1471 nm and supports data

4+2 channel CWDM, fiber optic cassette modul, SM, 2x

Fiber optic module with a built-in CWDM multiplexer and demultiplexer, terminated in LC/PC connectors. The module should be mounted in a 1U or 3U panel.

7830345 | CWDM Add/Drop Multiplexer, 1471-1491 nm | ANDREW

CWDM Fiber Optical Module, Add/Drop Multiplexer, 1471-1491 nm, LC/PC, 2 channels

CWDM Solution Guide

Corning Optical Communications reserves the right to improve, enhance, and modify the features and specifications of Corning Optical Communications products without prior notification.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Contact Us

Continue your research online:

Website: https://fdsoluciones.es
Technical inquiry: https://fdsoluciones.es/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved