
40G Optical Receiver Agent



Overview

The Optilab PR-40G-M is a high speed photo receiver module. Featuring 30 GHz bandwidth and 3000 V/W differential conversion gain, this module can be used in digital application as high as 40 Gbps. Trusted by 260K+. DESIGNED FOR USE IN 40 GIGABIT ETHERNET APPLICATIONS. COMPLIANT WITH THE QSFP MSA AND IEEE 802. 3BA Amphenol provides a series of 40G QSFP+optical module products, including SR4, eSR4, IR4, LR4, ER4 lite, AOC and AOC breakout series. This series of products adopts LC or MPO optical port and is. DSC-R404HG - Electrical Return Loss: For busy test stations or student labs, where users of different experience levels might be handling high value opto-electronics that are easily damaged by mishandling, order your photodiode to be mounted in the Lab Buddy. Featured products such as QSFP-SR4-40G modules and QSFP-LR4-40G modules are also available for choice. 652 single-mode optical fibers (SMF). several kilometers, no EDFA and dispersion compensation modules (DCM) are required. MACOM serves customers with a broad product portfolio that incorporates.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Article Content

40G QSFP+ Transceiver Modules | Optical Transceivers

FS 40G QSFP+ optical transceiver module solutions offer a full range of QSFP+ modules from 150m to 80km reach, and used for high-density switching, routing and data center applications.

40Gb/s QSFP+ Transceiver | Optical Interconnect

Amphenol provides a series of 40G QSFP+optical module products, including SR4, eSR4, IR4, LR4, ER4 lite, AOC and AOC breakout series.

40Gb/s (PIN) + TIA Optical Receivers

40 Gb/s PIN + TIA Optical Receivers ... For busy test stations or student labs, where users of different experience levels might be handling high value opto-electronics

40G Optical Transceivers and Cables Portfolio | FS

The series of product adopts LC or MTP/MPO connector and operates over Single Mode or Multimode optical fiber. They can be used for connections from 150m up to 40km and are suitable for 40G

High Speed Photoreceivers

MACOM offers 40G and 50G amplified PIN photoreceivers with high responsivity PIN photodiodes usable from 1200 – 1650 nm. These products are available in butterfly packages with single-mode

Cisco 40GBASE QSFP Modules Data Sheet

It enables high-bandwidth 40G optical links over 12-fiber parallel fiber terminated with MPO/MTP multifiber female connectors. It can also be used in a 4x10G mode for interoperability with

40G InGaAs Photodiodes and Optical Receivers

40G InGaAs Photodiode and Optical Receiver Lab Buddy Instrumentation: Put any of Discovery''s 40G photodiodes or photoreceivers in our Lab Buddy Instrument!

40 Gb/s PhotoReceiver Module – Optilab

The Optilab PR-40G-M is a high speed photo receiver module. Featuring 30 GHz bandwidth and 3000 V/W differential conversion gain, this module can be used in digital application as high as 40 Gbps.

InGaAs PIN-TIA Photoreceiver Up to 40Gbps

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

KY-PT series PIN-TIA Optical receiver use high-performance InGaAs Photodiode with a low noise transimpedance amplifier, which has the characteristics of high bandwidth, high responsivity, flat

Arista 40G FAQ

A. Arista supports a full range of both copper cables and optical transceivers for 40GbE, compliant to the IEEE standards. For copper both QSFP+ to QSFP+ (40G to 40G) and QSFP+ to SFP+ (40G to

PR-40G-M 40 Gb/s Photoreceiver

PR-40G-M 40 GBit/s Photoreceiver The Optilab PR-40G-M is a high speed photoreceiver module. Featuring 30 GHz bandwidth and 3000 V/W differential

40G QSFP Optical Transceiver

T1-QSFP-40G-SR4 is a four-channel, pluggable, parallel, fiber-optic QSFP+ transceiver for InfiniBand QDR/DDR/SDR applications. The QSFP full-duplex optical module offers 4 independent transmit and

40G DPSK DQPSK Balanced Optical Receivers

The DSC-R410 balanced receiver is ideally suited for apps up to 40 Gb such as DPSK, DQPSK and Dual Polarization DPSK. It is available in two configurations: balanced receiver module and plug-and

Pluggable Transceivers Installation Guide

For a complete listing of compatible cables and optical transceivers, see the Extreme Optics Compatibility website. Transmission distances are provided as a nominal guide only. To determine

QSFP+ 40G LR4 Explained: Your Ultimate Guide to 40G Long-Reach Optics

QSFP+ 40G LR4 enables high-speed, long-range data transfer for data centers, enterprises, and telecoms, supporting reliable 40G network growth in 2025.

Cisco 40GBASE QSFP Modules Data Sheet

Cisco QSFP-40G-SR-BD (40G BiDi) The Cisco QSFP 40-Gbps BiDirectional (BiDi) transceiver (Figure 1) is a pluggable optical transceiver with a duplex LC connector interface for short

DP-QPSK 100 Gb/400 Gb Coherent Optical Receiver Lab Buddy

Description: The DSC-R413 is an O/E instrument designed to convert DP-QPSK optical data to differential electrical signals. The R413 offers several user-adjustable characteristics such as RF

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

PT-40G-PLR4-31

2. GENERAL DESCRIPTION Profitap PT-40G-PLR4-31 is a Four-Channel, Pluggable, Parallel, Fiber-Optic QSFP+ Transceiver for InfiniBand QDR/DDR/SDR, 10G/8G/4G/2G fiber channel and SAS

Contact Us

Continue your research online:

Website: https://fdsoluciones.es
Technical inquiry: https://fdsoluciones.es/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved