

# Configuration of Layer 3 Switches in IUV Core Data Center



## Overview

All Ethernet ports are switched interfaces by default. You can change this default behavior with the CLI setup script or through the system default switchport command.

## Key Takeaways

Layer 3 switches in the IUV Core Data Center should be configured to provide high-speed interconnects, VLAN routing, redundancy, and scalable aggregation for multiple server and access modules.

## Core Layer Design

The core layer in a data center serves as the high-speed backbone connecting multiple aggregation modules and linking to the campus core, WAN, and Internet edge. It typically uses 10 Gigabit Ethernet (10GE) interfaces, often bundled in 4-8 link EtherChannels for high throughput and redundancy. Core switches are configured at Layer 3, enabling inter-VLAN routing and CEF-based load balancing to optimize traffic distribution.

The core layer should support scalability for multiple aggregation modules and provide burst traffic adaptability. Layer 3 Switch Configuration Steps  
Enable Layer 3 Mode on Interfaces  
Each interface connecting to aggregation modules or other core switches should be switched to Layer 3 mode. On Cisco Catalyst switches, this is done using: `CodeCopyinterface GigabitEthernet0/1no switchportip address 10.`

`0. 0. 1 255.`

255. 255. 0 no shutdown For multiple interfaces, EtherChannel (LACP) can be configured and switched to Layer 3 mode to increase bandwidth and redundancy.

### Configure VLA

Ns and SVIs Create VLANs for each functional zone or server farm and assign Switched Virtual Interfaces (SVIs) for routing: CodeCopyvlan 10name Server\_Farm\_Ainterface Vlan10ip address 10. 10. 10.

1 255. 255. 255.

0 no shutdown SVIs act as default gateways for devices in each VLAN, enabling inter-VLAN routing. Routing Protocols Deploy dynamic routing protocols such as OSPF or EIGRP to propagate routes between core and aggregation layers: CodeCopyrouter ospf 1network 10. 0.

0. 0 0. 255.

255. 255 area 0 This ensures fast convergence and redundancy in case of link failures. Redundancy and High Availability Core switches should be deployed in pairs with HSRP or VRRP for gateway redundancy.

### Ether

Channels between core and aggregation switches provide link-level redundancy.

### Advanced Features

#### Enable CE

F hashing for Layer 3 load balancing across multiple links.

#### Implement Qo

S policies to prioritize critical data center traffic. Configure access control lists (ACLs) for inter-VLAN security and traffic segmentation.

### Best Practices

Use dedicated Layer 3 interfaces for core-to-aggregation links rather than relying on Layer 2 trunks. Test hash algorithms for load balancing before production deployment to ensure even traffic distribution. Maintain high port density and oversubscription planning to accommodate server farm growth.

Integrate value-added services (firewalls, load balancers, SSL offload) at the aggregation layer while keeping the core layer optimized for high-speed packet switching. By following these steps, the IUV Core Data Center can achieve a scalable, high-performance, and resilient Layer 3 switching environment that supports inter-VLAN routing, redundancy, and efficient traffic management across multiple aggregation modules.

## Article Content

### Configuring Layer 3 Interfaces

All Ethernet ports are switched interfaces by default. You can change this default behavior with the CLI setup script or through the system default switchport command. You can assign an IP address to the

### Inter-VLAN Routing using Layer 3 Switches (4.3)

In this post, we'll explore how to configure a Layer 3 switch to handle Inter-VLAN routing, turning your flat network into a high-performance routed architecture.

### Data Center Architecture Overview

The access layer network infrastructure consists of modular switches, fixed configuration 1 or 2RU switches, and integral blade server switches. Switches provide both Layer 2 and Layer 3 topologies,

### InterVLAN routing using Layer 3 switch | NetworkAcademy.IO

In this lesson, we will learn to configure a multilayer switch (also called Layer 3 switch) to perform inter-VLAN routing, which was previously done using an actual router.

### Data Center Connectivity Design

A Two-Tier data center network implements aggregation and Layer 3 services in a data center core layer, and endpoint connectivity in a Layer 2 access layer. All access switches are Layer

### Layer 3 Switches Explained: Architecture, Routing Logic, Use Cases,

A Layer 3 switch is a network device that combines Layer 2 switching and Layer 3 routing. It can forward traffic based on MAC addresses inside the same network and route traffic based on IP

### Modern Data Center Network Architecture: Leaf-Spine

A 3-tier architecture uses three layers of switches: access, aggregation (distribution), and core, where access switches connect servers, aggregation switches

### MS Layer 3 Switching and Routing

To start using layer 3 routing, navigate to the Switching > Configure > Routing & DHCP page. Alternatively, you could go to Switching > Monitor > Switches and click on the switch to be

### Data Center Design: Basic 3 Layers, Core, Aggregation, and Access

The layering is mainly based on the principle of internal and external partial flow, and the data center network is divided into a standard three-layer structure of core layer, aggregation layer

Connecting Multiple switches to core : r/networking

I think you may be underwhelmed by how much data you're not moving. I've worked in large manufacturing facilities where the Core is connected to Distribution switches and they connect the

The Network DNA: Networking, Cloud, and Security

Master networking, cloud, and security with in-depth analysis, tutorials, and research. Stay ahead of the curve with our expert tech blog.

Cisco Data Center Networking Licensing

Cisco Data Center Networking Subscriptions Transform data center networks with Cisco tiered licensing Simplify Cisco Nexus One operations with flexible data

Enterprise High-Availability: VRRP, MLAG & ECMP Explained

The Core Layer (ECMP): Deploy high-performance Huawei CloudEngine or Ruijie 800G core switches. Run OSPF/BGP with ECMP to ensure massive routing capacity and Active/Active pathing to your

Network Configuration and Administration: A Complete Overview

Modern organizations operate across multiple offices, cloud environments, remote work setups, SaaS platforms, and hybrid data centers. Without structured Network Configuration and

ITPro Today, Network Computing, IoT World Today combine

ITPro Today, Network Computing and IoT World Today have combined with TechTarget . The page you are looking for may no longer exist.

Secure VLAN configuration: a practical guide and best practices

Network architecture and design with VLANs In medium and large networks it is common to use a three-layer topology Core, distribution, and access layers. Each layer has a role,

Ethernet Switches

Fortinet's Industrial Ethernet Switch Solutions are high-performance, cost-effective, and secure. Shop Fortinet's commercial ethernet switches with port-level network access security.

Gartner Business Insights, Strategies & Trends For Executives

Gain strategic business insights on cross-functional topics, and learn how to apply them to your function and role to drive stronger performance and innovation.

#### Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

## Contact Us

Continue your research online:

Website: <https://fdsoluciones.es>

Technical inquiry: <https://fdsoluciones.es/project-enquiry.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

