Configuring the gateway on a Layer 3 core switch



Overview

To start using layer 3 routing, navigate to the Switching > Configure > Routing & DHCP page. Alternatively, you could go to Switching > Monitor > Switches and click on the switch to be configured. On. If the L3 switch is the gateway for clients downstream subnets, any upstream firewall must be configured with a static route to that downstream subnet. If the firewall is configured with a VLAN interface for this downstream subnet, the firewall may receive incorrectly tagged traffic from this. Layer 3 Routing allows a UniFi Switch to route traffic between VLANs and to other destinations using static routes. It is possible use L3 Routing with a UniFi Gateway or third-party gateway. You can configure a port as a Layer 2 interface or a Layer 3 interface. A routed interface is a physical port that. The latest Cisco Catalyst Switches are equipped with the Enhanced Multilayer Image (EMI), which can work as a Layer 3 device with full routing capabilities, also known as a multi-layer switch (MLS). Below are some of the Cisco Catalyst Series switches with Layer 3 functionalities: A Layer 3 Switch. On a Layer3-capable switch, the port interfaces work as Layer 2 access ports by default, but you can also configure them as “ Routed Ports ” which act as normal router interfaces.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Article Content

Layer 3 Switch Example

This article outlines a basic example of how layer 3 routing functionality on MS series switches could be implemented. Before proceeding, please refer to the Layer 3 Switch Overview for general information

Layer 3 Routing – Ubiquiti Help Center

Layer 3 Routing allows a UniFi Switch to route traffic between VLANs and to other destinations using static routes. It is possible use L3 Routing with a UniFi Gateway or third-party gateway. Note: ...

Configuring Layer 3 Interfaces

All Ethernet ports are switched interfaces by default. You can change this default behavior with the CLI setup script or through the system default switchport command. You can assign an IP address to the

Cisco Layer 3 Switch InterVLAN Routing Configuration

Below is a diagram that we can use as a reference in understanding how to configure Inter-VLAN routing and test inter-switch connectivity across the network before configuring its routing capability.

How to configure a Cisco Layer 3 Switch-InterVLAN Routing Without

On the Layer3 Switch, for Vlan10 we will create an SVI with IP address 10.10.10.10 and for Vlan20 an SVI with IP address 10.20.20.20. These two IP addresses will serve as the default gateway

Example for Configuring a Layer 3 Switch to Work with a Router for ...

Layer 3 switches can work at Layer 2 and Layer 3 and be deployed at the access layer or aggregation layer as user gateways. Switch configurations used in this example apply to all versions

InterVLAN routing using Layer 3 switch | NetworkAcademy.IO

In this lesson, we will learn to configure a multilayer switch (also called Layer 3 switch) to perform inter-VLAN routing, which was previously done using an actual router.

Inter-VLAN Routing using Layer 3 Switches (4.3)

In this section, you configure inter-VLAN routing using Layer 3 switches. Modern enterprise networks rarely use router-on-a-stick because it does not scale easily to meet requirements. In these very

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Switch Stacks

Meraki switches allow for physical stacking on select switch models so you can easily manage all of your switches and get physical redundancy in the deployments that need it.

Configure Ethernet Virtual Connections on Catalyst 8000 Routers

You can configure the Core_Router to bridge packets that do not need to be routed and, you can also configure a single interface to act as the default gateway for both hosts. This can be donewith

Router Configuration With Cisco Packet Tracer

Step-2 (Configuring PCs): Assign IP Addresses to every PC in the network. Select the PC, Go to the desktop and select IP Configuration and assign an IP address, Default gateway,

Changes with Storage on Cloud and Storage Classification in VMM

First published on TECHNET on May 19, 2014 Storage Classification was introduced in System Center 2012 Virtual Machine Manager (VMM 2012) to provide the...

How can I reduce or decrease the size of a PDF for cloud printing on

I need to print PDF learning materials for my kids but the EPSON printer does not support PDF files larger than 50MB for cloud print. The current PDF is over that limit, so it can''t be uploaded

Free Markdown to HTML Converter

Convert Markdown to HTML Paste or type your markdown and see it rendered as HTML. Download or copy the resulting HTML. Coming Soon! This page will also allow you to: Save stylesheets to use

ITPro Today, Network Computing, IoT World Today combine

ITPro Today, Network Computing and IoT World Today have combined with TechTarget . The page you are looking for may no longer exist.

GitHub Copilot LLM Gateway

GitHub Copilot LLM Gateway A robustness layer for running self-hosted open-source models inside GitHub Copilot Chat — built for the models and servers that don''t quite behave. Do I need this, or is

Windows 11 preview is now available on Azure Virtual Desktop

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Azure Virtual Desktop has become a popular cloud VDI platform to run desktops and apps in the cloud and deliver a full Windows experience to users virtually anywhere. Organizations

Networking overview | Docker Docs

Published ports When you create or run a container using docker create or docker run, all ports of containers on bridge networks are accessible from the Docker host and other containers connected

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://fdsoluciones.es
Technical inquiry: https://fdsoluciones.es/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved