Fiber Optic Circulator 1550



Overview

Thorlabs' 1550 nm SM Fiber Optic Circulators are available unterminated, with FC/PC connectors, or with FC/APC connectors. Available with a center wavelength of 1064, 1310 (O-Band), or 1550 nm (C-Band), these circulators are fast axis blocked and hence are. The OC Series 1310/1550 Optical Circulators are non-reciprocal devices that redirect light at 1310/1550 nm from port-to-port in only one direction while minimizing back reflection and back scattering in the reverse directions for any polarization state. They perform a similar function as an isolator, protecting the input fiber from return power, but also allowing the. 1310/1480/1550nm High Power Fiber Circulator, suitable for up to 20W applications, features low insertion loss, high return loss, and high isolation, ensuring high reliability and stability. This makes it an ideal choice for EDFA & Raman Amplifiers, fiber sensors, and fiber lasers, where.

Article Content

Polarization-Maintaining Fiber Optic Circulators

Thorlabs'' 1550 nm PM Fiber Optic Circulators are available unterminated, with FC/PC connectors, or with FC/APC connectors. The FC/PC and FC/APC

SM Fiber Optical Circulator 1310nm & 1550nm

The OC Series 1310/1550 Optical Circulators are non-reciprocal devices that redirect light at 1310/1550 nm from port-to-port in only one direction while minimizing

1310/1480/1550nm HP Fiber Circulator | SIMTRUM

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Boost fiber optics with SIMTRUM''s 1310/1480/1550nm Circulator: High power, low loss, ideal for EDFAs, amplifiers, and lasers.

High Power Fiber Optical Circulator 1310nm & 1550nm

The excellent characteristics of this product make it an ideal choice for application in fiber amplifier systems, pump laser diodes, and optical fiber sensors. This

1550nm 3 Port SM Fiber optical Circulato-Ideal-Photonics Inc

Ideal-photonics''s 1550 nm SM Fiber Optic Circulators are available unterminated, with FC/PC connectors, or with FC/APC connectors. The FC/PC and FC/APC connectors have a 2 mm narrow

Optic Circulator 1310~1550nm

This Optical Circulator can be used in Optical Amplifiers, FBG Applications, Dispersion Compensation, Fiber Sensors and has features of Low Insertion Loss

With the current valuation of 14.3% CAGR, this report provides a ...

The Multimode Optical Circulators market is segmented by wavelength and application. By wavelength, it includes 1310 nm, 1550 nm, and Other. The application segments encompass Fiber

Glossary of fiber optic network terms

The distortion of mode due to the geometric properties of the waveguide. Wavelength The optical term for frequency. Fiber-optics generally uses the 850

Fiber WDMs, Combiners, Splitters and Couplers

Custom designs combining circulators, polarizing splitters and non-polarizing splitters in the same package are routinely manufactured. Splitters can be made

The Fiber Optic Association

Other groups may have fiber optic standards also: ANSI is the governing bodies for standards in the US, NIST provides primary standards, IEEE has standards for networks like Ethernet, IWCS has

FIBER OPTIC INTERROGATION SYSTEM FOR MULTIPLE

The fiber optic interrogation system 100 of the present application comprises at least one controllable laser source unit 102, a modulator 104 attached to the controllable laser source unit 102, an amplifier

High efficiency respiratory rate monitoring fiber optic sensing probe ...

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

High efficiency respiratory rate monitoring fiber optic sensing probe based on chitosan moisture sensitive film and temperature drift compensation method

1x8 Single Mode Fiber Optic Splitters

Mount to an Optical Table with the FCQB Mounting Base (Available Below) Thorlabs'' Single Mode 1x8 Fiber Optic Planar Lightwave Circuit (PLC) Splitters allow a user to split a single input signal evenly

How to Choose an OTDR for Fiber Optic Testing: Complete 2026 Guide

Learn how to choose the right OTDR for fiber optic testing. Compare wavelengths, dynamic range, distance range, and key specs to match your network type and budget.

High Power Fiber Optical Circulator 1310nm & 1550nm

The 1310/1550 nm high power optical circulator is designed for high power applications. This non-reciprocal device redirects light at 1310/1550 nm wavelengths from port-to-port in only one direction

PM Circulator 1310/1550

Product Description Series 1310/1550 PM Optical Circulator is a non-reciprocal device maintains polarization while redirecting light at 1310/1550 nm from port-to-port in only one direction while

CIR1550PM-FC

The CIR1550PM-FC from Thorlabs Inc is a Fiber Optic Circulator with Insertion Loss 40 dB, Return Loss >50 dB, Optical Power 300 mW.

1550nm 3-port High Power PM Optical Circulator-30W

1550nm 3-port High Power PM Optical Circulator-30W The 1550nm 3-port High Power PM Optical Circulator-30W is a compact, high performance light wave Polarization Maintaining component that

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Contact Us

Continue your research online:

Website: https://fdsoluciones.es
Technical inquiry: https://fdsoluciones.es/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved