
Leakage protection for three-level distribution boxes



Overview

Each distribution box contains circuit breakers, fuses, and leakage current devices, which control and protect the electromechanical equipment and lighting circuits they serve.

Key Takeaways

Three-level distribution boxes require two-level leakage protection, with leakage protectors installed in both the main distribution box and the switch box, following specific rated currents and response times.

Overview of Three-

Level Distribution and Two-Level Leakage ProtectionA three-level distribution system typically includes: Main distribution box (first level) – located near the power source. Distribution box (second level) – installed near concentrated electrical equipment or loads. Switch box (third level) – final junction for individual electrical appliances, either fixed or movable.

Two-level leakage protection means that leakage protectors are installed at: The main distribution box (first level)The switch box (third level) This ensures that both the overall system and individual circuits are protected from leakage currents.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Leakage Protector Specifications

Main distribution box: Rated leakage current: 50–100 mARated leakage action time: greater than 0. 1 s Switch box: Rated leakage current: ≤30 mARated leakage action time: ≤0. 1 sIn wet or corrosive environments: rated leakage current ≤15 mA, action time ≤0.

1 s Selection criteria: Leakage protectors must be sensitive, reliable, and matched to the load. Splash-proof or waterproof models are required for damp or corrosive locations.

Installation and Distance Requirements

Distance between distribution box and switch box: ≤30 metersHorizontal distance between switch box and controlled electrical equipment: ≤3 metersEach electrical device should have its own dedicated switch and leakage protection, following the principle of “one machine, one switch, one leakage, one box, one lock”.

Material and Construction Requirements

Distribution boxes and switch boxes should be made of cold-rolled steel plates (1. 2–2. 0 mm thick) or flame-retardant insulating materialsBoxes must be rainproof, dustproof, and suitable for outdoor useElectrical appliances inside the boxes must be reliable, intact, and neatly wired.

RationaleThree-level distribution with two-level leakage protection is adopted to: Adapt to dispersed and concentrated loads on construction sitesEnsure short-circuit, overload, and leakage protection at multiple levelsComply with temporary power regulations and safety standards for construction electricity. This configuration ensures maximum safety, prevents electrical hazards, and allows for efficient management of temporary power systems.

Article Content

Where is the leakage protection in the three-level distribution box

Each distribution box contains circuit breakers, fuses, and leakage current devices, which control and protect the electromechanical equipment and lighting circuits they serve.

Design of two-level leakage protection for three-level power ...

There are two levels of leakage protection, which are the main circuit or sub-circuit in the main distribution box at one level and the switch box at one level.

Residual Current Devices (RCDs)

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

An accurate protection of people and electrical equipment against leakage currents can be achieved by installing Residual Current Devices (RCDs).

If you don''t understand the third-level power distribution and the ...

The shell of the distribution box (cabinet) is made of cold-rolled steel plate, which is rainproof, dustproof, and outdoor type. The thickness of the steel plate meets the standard requirements and is durable.

RD series

The RD series is designed for leakage current detection, protection and monitoring functions. It is composed by DIN-rail mounted RD2 and RD3 relays.

Configuration Standards For Distribution Boxes (cabinets) At All Levels

The distribution box (cabinet) is suitable for temporary power supply at the construction site and should meet the requirements of "three-level power distribution, two-level leakage

New surge protective devices

In large installations, several SPDs are required for maximum overvoltage protection efficiency, especially if the SPD at the supply end has a Up protection level higher than 1.5 kV (EN 62305 and

Detailed introduction of safety requirements for distribution box

The power switch installed in the distribution box and switch box shall have the functions of short circuit protection and overload protection, and its rated value and action setting value shall

What is Level 1, Level 2 and Level 3 distribution box

Three level protection refers to: on-site construction of electricity must be done in the general distribution box, distribution box and switch box to install leakage protection.

Leakage Protection Switch

The leakage protection switch is mainly used for protection of building lighting and power distribution system, in line with standards of GB16917.1 and IEC61009-1. The product has passed the national

ELCB Explained: How It Protects Electrical Systems

What is an Earth Leakage Circuit Breaker? An earth leakage circuit breaker (ELCB), also known as an earth leakage switch or earth leakage protector, is an electrical safety device. It is

Reuters | Breaking International News & Views

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Find latest news from every corner of the globe at Reuters , your online source for breaking international news coverage.

The difference between the first,second,and third levels of ...

Third level distribution box: refers to the final junction box of each electrical appliance, which can be movable and fixed. Remember that the leakage protection switch is the last one, and

Where is the leakage protection in the three-level distribution box

Three level protection refers to: on-site construction of electricity must be done in the general distribution box, distribution box and switch box to install leakage protection.

SAFEHOUSE GUIDE TO DISTRIBUTION BOARDS,

SAFEHOUSE GUIDE TO DISTRIBUTION BOARDS, ISOLATORS AND EARTH LEAKAGE UNITS The distribution board in any building contains

Installation of leakage protection device

The location of the leakage protection device in the power line, in principle, must be installed on the power supply side of the distribution panel or in the distribution panel, except for the ...

Detailed Explanation of Tiered Surge Protection for Distribution Boxes ...

In lightning protection, the surge protection device in distribution boxes plays a crucial role. According to the principle of graded lightning protection, and based on the likelihood of a building be...

The Meaning and Function of Primary, Secondary, and Tertiary ...

Forms part of the three-level protection system. Features inner and outer doors, powder-coated exteriors, and rainproof tops for outdoor use. Tertiary Distribution Box: The system includes a

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Contact Us

Continue your research online:

Website: https://fdsoluciones.es
Technical inquiry: https://fdsoluciones.es/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved