Routing for Switch SVI Ports



Overview

This guide configures inter-VLAN routing on a Layer 3 switch with SVIs, end to end on Cisco IOS: enabling IP routing, building one SVI gateway per VLAN, and verifying that traffic routes between VLANs through the switch. Every command and all output come from a real lab. It is the production answer. In this sample chapter from CCNA 200-301 Official Cert Guide, Volume 1, Wendell Odom discusses the configuration and verification steps related to three methods of routing between VLANs with three major sections: VLAN Routing with Router 802. e between different LANs or WANs) requires the use of a router. Layer 2 VLANs create what is known as a single broadcast domain, which simply means that when a broadcast message is sent within the same. int vlan 10,50 are the SVI's on L3 switch vlan 50 is the native vlan on trunk link towards (router, FW) Routed port is configured on the physical interface with 10. 1/24 Problem is that I can reach routed port sourcing from both SVI's but no from the device being inside vlan 10 Taking tcpdump. Normally, Routers are used to divide the broadcast domain and switches (at layer 2) Operate in a single broadcast domain but Switches can also divide the broadcast domain by using the concept of VLAN (Virtual LAN). VLAN is the logical grouping of devices in the same or different broadcast domains.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Article Content

Configure Layer 3 Switch SVI Routing | ComputingForGeeks

This guide configures inter-VLAN routing on a Layer 3 switch with SVIs, end to end on Cisco IOS: enabling IP routing, building one SVI gateway per VLAN, and verifying that traffic routes

VLAN Routing with Layer 3 Switch SVIs

Configuring Routing Using Switch SVISVerifying Routing with SVISTroubleshooting Routing with SVISThere are two big topics to investigate when troubleshooting routing over LANs with SVIs. First, you have to make sure the switch has been enabled to support IP routing. Second, the VLAN associated with each VLAN interface must be known and active on the local switch; otherwise, the VLAN interfaces do not come up. First, about enabling IP routing, ...See more on ciscopress Cisco Press

VLAN Routing with Layer 3 Switch Routed Ports - Cisco Press

When a Layer 3 switch needs a Layer 3 interface connected to a subnet, and only one physical interface connects to that subnet, the network engineer can choose to use a routed port instead of an SVI.

What is Cisco Switch Virtual Interface (SVI)

In Layer 3 switches, you must enable routing globally (using “ ip routing ” command) in order for SVI to work. Many people compare SVI with routed-ports. Here are the differences: An SVI

Routing between SVI and routed port on router

Vlans 30,40,50 just existing on the switch and going to the router thru trunk and they have their own subinterfaces created. I am looking for a way to use another vlan just for connectivity

Inter VLAN Routing by Layer 3 Switch

SVI on the layer 3 switch provides both management and routing services while SVI on layer 2 switch provides only management services like creating VLANs or telnet/SSH services.

Inter-VLAN Routing — Layer 3 Switch SVI | Cisco IOS | NetsTuts

Step-by-step Cisco IOS lab to configure SVIs on a multilayer switch for inter-VLAN routing at wire speed. Full topology, ip routing command, and verification. CCNA lab guide.

Best Practices for Inter-VLAN Routing in CISCO

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

In this discussion, lets explore the best ways to set up Inter-VLAN Routing on Cisco devices, using simple explanations and clear examples to help configure network efficiently.

MS Layer 3 Switching and Routing

Routed ports are a great option for connecting switches in core/distribution network for inter-switch routing and are ideal for point-to-point links. Routed ports, being physical interfaces,

InterVLAN Routing

In this lesson you will learn about the different options there are for routing between VLANS: Router on a stick, SVI interface or L3 interfaces.

Layer 3 Switch Example

Configuring the Switch Ports Additional Considerations Switch Management IP and Layer 3 Interfaces (SVIs) Related KBs This article outlines a basic example of how layer 3 routing functionality on MS

How to Configure a Cisco Switch (step by step)

If you''re looking to configure a switch for the first time, this post is for you. Learn step-by-step configuration commands for Cisco IOS Switches.

Camera VLAN Setup Guide 2025 | Secure IP Camera Network

Step-by-step VLAN configuration for IP cameras using 802.1Q, PoE switches, and firewall routing. Secure surveillance network setup with NVR access today now

Virtual LAN (VLAN)

Switch (config) interface fa0/1 Switch (config-if) switchport mode access Switch (config-if) switchport access vlan 3 Here, port Fa0/0 is assigned to VLAN 2 and port Fa0/1 is assigned to VLAN

Routed Port vs. Switch Virtual Interface (SVI)

Routed Port vs. Switch Virtual Interface (SVI) Many years ago, networks consisted of repeaters, bridges and router. Switches are the successors of the bridges. A switch is nothing else than a multiport

SVI vs Routed Port

So if I have a single port going from a switch to a router (Not for the purpose of interVlan routing on a switch, ROAS). I can either make the port on the switch a routed port or set it as an access port

SVI vs. Routed Port: The Key Differences in Layer 3 Switching

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved

Both Switched Virtual Interfaces (SVIs) and Routed Ports are methods used by Layer 3 switches (or multilayer switches) to perform routing between different IP subnets. However, they are

How to Configure SVI in Cisco Packet Tracer (Step-by-Step)?

Learn how to configure SVI (Switch Virtual Interface) in Cisco Packet Tracer step-by-step. Understand inter-VLAN routing on a Cisco switch.

Switching: Routed Ports and Switched Virtual Interfaces (SVIs)

It is configured on a port connected to a router. SVI''s support both routing and switching protocols, while routed ports do not support any layer 2 protocols (STP). An SVI is created by the interface VLAN

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://fdsoluciones.es
Technical inquiry: https://fdsoluciones.es/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 FD SOLUCIONES OPTICAL SYSTEMS - All rights reserved